



Wholesale Price List OCT 2023

www.opushardware.com

SECTION 3 | COMMERCIAL DOORS, PARTITIONS & PATCH FITTINGS

Product	Page
Door Springs & Closers	3 - 4
Patch Fittings	3 - 11
Patch Components	6 & 10
Indicator Locks for Swing Doors	12
Lever Locks or Latchsets	13
Vienna Hydraulic Door Hinges	15
Door Rails and Components	16 - 17
Pulls & Door Handles	See Catalogue Section 5 (Handles & Pulls)
Sliding Doors & Roller Systems	See Catalogue Section 4 (Sliding Door Systems)
Glazing Channel & End Caps	18 - 20
Fin Brackets	21
Door Seals	22 - 23
Packers & Setting Block	24
Patch Fitting Application Guide	25

Product availability

Popular Item (Usually readily available, ex stock)



Slower Mover/ Lead Time applies (Check stock status)

Limited Stocks Available

*Please note, availability chart is only an indication of stock expectation and is not guaranteed. (Unforeseen/unusual demand or popularity can affect stock levels)



MORITZ SELF-CLOSING PATCH

PRODUCT

```
DESCRIPTION
```



Moritz EN3/EN5 Hydraulic Self-Closing Patch

Bottom mounted to timber, steel or concrete. Suits 10-15mm toughened safety glass.

Includes base pivot plate


(Standard) EN3 - Residential and commercial internal use only. Applicable for single or double doors with a width of 750mm to 1000mm and weight up to 100kg each.


(Heavy Duty) EN5 - Residential and commercial internal & external use. Applicable for single or double doors with a width of 1000mm (Max External) to 1250mm (Max Internal) and weight up to 100kg each.

Used in conjunction with a standard top patch fitting and floor stop.

Multiple adjustments and settings for closing and breaking speed.

5 year Warranty





Base plate hole locations



FLOOR/OVERHEAD DOOR SPRINGS

PRODUCT		DESCRIP	TION		
	EFS840/MFX8 Standard Floo	-			
	Double action floors Maximum door weig spring and 800mm o	ht 100kg, with widt		a standard	
	2 speed hydraulic control; closing adjustment 130°–15°, latching adjustment 15°–0°				
	Spindle heights from STD to 50mm extension (5mm increments). Use with frameless patch fittings and rails.				
130/105	Warranty 5years or 500,000 cycles				
324/358	STRENGTH	TYPE	CODE	PRICE	
* *	15NM Weak	Non Hold Open	EFS840NHOW	•	
		Hold Open	EFS840HOW	•	
306/341		Non Hold Open	EFS840NHO	•	
108/78 *1st Measurement is Standard 84 Series Spring *2nd Measuremement is Heavy Duty 80 Series Spring (Below)	25NM Standard	Hold Open	EFS840HO	•	
PRODUCT	DESCRIPTION				



PRODUCT

BTS80 Heavy Duty Floor Spring

Double action floorspring with Stainless steel (cover plate). Maximum door weight 300kg, with widths up to 1400mm. Selective multi-point hold open adjustable between approximately 75° and 175°. Mechanical backcheck at approximately 85° and 165°. Variable closing force 53 Nm. Spindle heights from STD to 50mm extension (5mm increments). Use with frameless patch fittings and rails. Warranty 5years or 500,000 cycles

TYPE	CODE	PRICE		
Non Hold Open	BTS80NHO	ightarrow		
Hold Open	BTS80HO	•		
DESCRIPTION				

RTS85 Overhead Door Closer

Double action, 90° . Aluminium/wood fix Satin Stainless coverplate

Maximum door weight 110kg, widths up to 1000mm


TYPE	CODE	PRICE
Non Hold Open	RTS85NHO	•
Hold Open	RTS85HO	•




10/2023

STANDARD DOOR & PATCH FITTINGS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	HPT10/MP10 Bottom Patch Fitting	Polished Stainless	HPT10-PS	•
	Suitable for floorspring range and HPT26 free swing pivot	Satin Stainless	HPT10-SS	•
	Suits 10mm or 12mm glass. Adjustable pivot insert, Factory set at 55mm.	Black	НРТ10-ВК	•
	HPT20/MP20 Top Patch Fitting	Polished Stainless	HPT20-PS	•
	Suitable for HPT24, HPT25, HPT34, HPT40 and HPT41 pivots	Satin Stainless	HPT20-SS	•
	Suits 10mm or 12mm glass. Adjustable pivot insert, Factory set at 55mm.	Black	НРТ2О-ВК	•
	HPT22/MP22 Top Patch Fitting	Polished Stainless	HPT22-PS	•
	Suitable for RTS85 overhead closer. Suits 10mm or 12mm glass.	Satin Stainless	HPT22-SS	•
	Adjustable pivot insert, Factory set at 55mm. Reversable to 65mm	Black	HPT22-BK	•
	HPT100/XL10 Bottom Heavy Duty Patch	Polished Stainless	HPT100-PS	•
	Suitable for floorspring range and HPT26 free swing pivot	Satin Stainless	HPT100-SS	•
and an and	Suits 15mm to 19mm glass. Adjustable pivot insert.	Black	HPT100-BK	•
	HPT200/XL20 Top Heavy Duty Patch	Polished Stainless	HPT200-PS	•
	Suitable for HPT24, HPT25 and HPT400 pivots.	Satin Stainless	HPT200-SS	•
	Suits 15mm to 19mm glass. Adjustable pivot insert.	Black	НРТ200-ВК	•
	31/41mm	164mm		







5

DOOR & PATCH FITTINGS

PRODUCT	DESCRIPTION	FINISH/TYPE	CODE	PRICE
105mm	HPT24	Polished Stainless	HPT24-PS	•
O O	Plate mounted pin. Suitable for use with HPT20/HPT200 patch and RL2	Satin Stainless	HPT24-SS	•
2mm 28mm	and RL4 top rails	Black	HPT24-BK	•
60mm	HPT25	Polished Stainless	HPT25-PS	•
	8mm metric thread, Plated Steel 44mm diameter face washer	Satin Stainless	HPT25-SS	•
50mm	Suitable for use with HPT20 patch and RL2 and RL4 top rails	Black	НРТ25-РВК	•
100mm	HPT26 Free swing floor pivot Suitable for use with HPT10 and RL1 and RL3 bottom rails	Satin Stainless	HPT26-SS	•
100mm 45mm	HPT26 EXT5 Floor pivot bearings Free swing floor pivot. Suitable for use with HPT10 and RL1 and RL3 bottom rails, extended spindle	Satin Stainless	HPT26EXT5-SS	•
	HPT26CP Cover Plate	Satin Stainless	HPT26CP-SS	•
		Polished Stainless	HPT26CP-PS	•
	HPT28 Head Stop	Satin Stainless	HPT28-SS	•
50mm 16mm	Rubber infill stop. Available for single or double door installations. Specify HPT28S for single door	Polished Stainless	HPT28-PS	•
	HPT28D Head Stop	Satin Stainless	HPT28D-SS	•
100mm 16mm	Rubber infill stop. Available for single or double door installations. Specify HPT28D for double door	Polished Stainless	HPT28D-PS	•
	Floor Spring Spindles	Standard (30mm)	300544	•
	Suits floor springs, * Please specify if you require	5mm	300545	•
	Offset 3 degrees for single action LH or RH	10mm	300538	•
	3°	15mm	300539	ightarrow
	LH off set spindle	20mm	300540	•
	3°	25mm	300541	•
	RH off set spindle	40mm	300542	•
		50mm	300543	•



6

DOOR & PATCH FITTINGS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
31/41mm 52mm	HPT40/MP40 Over to Side Panel Pivot Patch Fixing with pivot pin. Adjustable	Polished Stainless	HPT40-PS	•
106mm	pivot insert. Suitable for use with HPT20/200 & with 10,12mm & 15,19mm glass. Pivot pin can be removed and replaced with a stop for single action door when this	Satin Stainless	HPT40-SS	
52mm	patch is used for an over to side	Black	НРТ4О-ВК	•
$36 \xrightarrow{10}{161} \xrightarrow{148}{34} \xrightarrow{1}{34}$		HEAVY DUTY XL Satin Stainless	HTP400-SS	•
31mm 52mm	HPT41/MP41 LH Over to Side Panel Pivot Patch including Fin	Polished Stainless	HPT41L-PS	•
$20 \qquad 20 \qquad 0 $	Adjustable pivot insert.	Satin Stainless	HPT41L-SS	•
		Black	HPT41L-BK	•
112mm 156mm 0 0 52mm	HPT41/MP41 RH Over to Side Panel Pivot Patch including Fin	Polished Stainless	HPT41R-PS	•
	Patch for over to side panel with fin at 90°. Suitable for use with HPT20 & with 10–12mm glass. Adjustable pivot insert.	Satin Stainless	HPT41R-SS	
$\begin{bmatrix} 60 \\ \hline \\ \hline \\ 10 \end{bmatrix} \begin{bmatrix} 60 \\ \hline \\ \hline \\ \hline \\ 30 \\ \hline \\ 150 \end{bmatrix} \xrightarrow{30}$		Black	HPT41R-BK	•



10/2023 SECTION 3 | COMMERCIAL DOORS, PARTITIONS & PATCH FITTINGS

DOOR & PATCH FITTINGS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
164mm	HPT30/34 Overpanel Pivot Patch	Satin Stainless	HPT30-SS	•
52mm 0 0 15mm	Fixing overpanel to wall fitted with pivot pin. use with HPT20.	Polished Stainless	HPT30-PS	•
	Suits 10–12mm glass. Adjustable pivot insert. Factory set at 55mm.	Black	НРТЗО-ВК	•
60mm	HPT30 (Patch only) HPT34 (Includes Backplate)	Satin Stainless	HPT34-SS	•
161 148		Polished Stainless	HPT34-PS	•
36 55 R 80 € 68 37		Black	HPT34-BK	•
106mm	HPT60 Overpanel to Side Panel Patch Fitting Suits 10mm & 12mm glass	Polished Stainless	HPT60-PS	•
106mm		Satin Stainless	HPT60-SS	•
106mm	HPT61 Overpanel to Side Panel Patch Fitting Suits 10mm & 12mm glass Includes removable single action door stop	Polished Stainless	HPT61-PS	•
10ómm 52mm	36 1 7336 36 7336 36 7336 36 73	Satin Stainless	HPT61-SS	۰
116mm	HPT70 Overpanel Patch incorporating Stops for Single Action Double Doors	Polished Stainless	HPT70-PS	•
52mm 26mm	Stops removable and reversible Suits 10mm & 12mm glass $\overbrace{30}^{40}$ $\overbrace{40}^{40}$ $\overbrace{30}^{30}$	Satin Stainless	HPT70-SS	•



8

PATCH LOCKS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
235mm	PL590 Bottom or Top Patch Lock Complete with lock and cylinders Specify cylinder combination	Polished Satin	PL590-PA	•
	e.g. Double cylinder, Cylinder/Turn, Single cylinder & Single turn Use with keeper LK590/GK590 Suits 10–12mm glass	Satin Stainless	PL590-SS	•
	PL590	Black	PL590-BK	۰
233mm 212 40 37mm 50mm	CPL590 Centre Patch Lock Complete with lock and cylinders Specify cylinder combination	Polished Satin	CPL590-PA	
	e.g. Double cylinder, Cylinder/Turn, Single cylinder & Single turn Use with keepers CPK590 and LK590 Suits 10–12mm glass	Satin Stainless	CPL590-SS	
	CPL590	Black	CPL590-BK	
	CPK590 Centre Patch Keeper	Polished Satin	CPK590-PA	
233mm 212 40 37mm 50mm	Use with CPL590 Suits 10–12mm glass	Satin Stainless	CPK590-SS	•
	CPK590	Black	СРК590-ВК	



10/2023 SECTION 3 | COMMERCIAL DOORS, PARTITIONS & PATCH FITTINGS

PATCH LOCKS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
		Chrome Plate	DC88-CP	•
DC88 Cylinder Double	DC88/CT88 Eurostyle	Satin Chrome	DC88-SC	•
CT88 Cylinder/	Cylinders Used with EL10	Chrome Plate	CT88-CP	•
Turn		Satin Chrome	CT88-SC	•
	LK590/GK590 Lockwood 590 Groundkeeper			
120mm 26mm	LK590 - Used with PL590 and CPL590 locks & rails	Stainless Steel	LK590	•
LK590	GK590 - Used with rail locks & PL590			
28mm / 42mm / GK590	GK590	Satin Silver Anodised	GK590	۰
			SC90	•
SC90 TK90 Single cylinder Turn knob	SC90/TK90/ER90/RS90 Lockwood accessories	Satin Silver	ТК90	•
	590 patch locks Used with rail locks	Anodised	ER90	•
ER90 RS90 Escutcheon rose Retaining screw			RS90	•
Slide option Glue-on option	374 Straddle Fix Bolt Lock Suitable for 10mm or 12mm thick	Slide Option	374SA	•
15mm 40mm 28mm	glass. No cut out of glass panel required. Silicon fixing. SSS Finish Tubular groundkeeper included Slide and glue-on options	Glue On	374GSA	•



PATCH LOCKS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	CPL590P Parrot Beak Patch For sliding doors Complete with lock and cylinders	Polished Satin	CPL59P-PS	•
	Specify cylinder combination e.g. Double cylinder, Cylinder/ Turn, Single cylinder & Single turn Use with keeper CPK590P Suits 10mm & 12mm glass	Satin Stainless	CPL59P-SS	•
WK590P	CPK590P Parrot Beak Keeper For sliding doors	Polished Satin	CPK590P-PS	•
	For sliding doors Use with CPL590P Suits 10mm & 12mm glass	Satin Stainless	CPK590P-SS	•
	EL10PL Top/Bottom Patch Lock Vertical bolt projection 20mm	Polished Satin	EL10PL-PS	•
166mm 166mm EL10K Keeper	Eurotype cylinders Specify cylinder combination e.g. double cylinder, cylinder/turn, single cylinder & single turn Suits 10mm or 12mm glass	Satin Stainless	EL10PL-SS	•
	EL10CPL Centre Patch Lock Vertical bolt projection 20mm Eurotype cylinders	Polished Satin	EL10CPL-PS	•
	Specify cylinder combination e.g. double cylinder, cylinder/turn, single cylinder & single turn. Suits 10mm or 12mm glass Striker box is available (code EL10CPK)	Satin Stainless	EL10CPL-SS	•




10/2023 SECTION 3 | COMMERCIAL DOORS, PARTITIONS & PATCH FITTINGS


INDICATOR LOCKS FOR SWING DOORS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
•	Indicator Lock Door to Wall (Glass Cut Out Required)	Polished Chrome	IL700C	•
0	For Toilet and Bathroom Doors. To suit 8mm and 10mm glass.	Satin Chome	IL700C	•
	Indicator Lock Door to Sidepanel	Polished Chrome	IL701C	•
	(Glass Cut Outs Required) For Toilet and Bathroom Doors. To suit 8mm and 10mm glass.	Satin Chome	IL701C	•
	Indicator Lock Door to Wall (No Glass Cut Out Required)	Polished Chrome	IL600C	•
	For Toilet and Bathroom Doors. To suit 8mm and 10mm glass.	Satin Chome	IL600C	•
	Indicator Lock Door to Sidepanel	Polished Chrome	IL601C	•
	(No Glass Cut Outs Required) For Toilet and Bathroom Doors. To suit 8mm and 10mm glass.	Satin Chome	IL601C	•





IL-701C




10/2023

LEVER LOCKS AND LATCH SETS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	Lever Lockset with Cylinder	Polished Stainless	LLJ-01-PS	•
	Locking to timber or aluminium jamb Specify 10mm or 12mm glass thickness	Satin Stainless	LLJ-01-SS	•
	Lever Lockset Locking to glass sidelight	Polished Stainless	LLG-02-PS	•
	Specify 10mm or 12mm glass thickness	Satin Stainless	LLG-02-SS	•
	Level Latchiset Latching to timber or aluminium jamb _ Specify 10mm or 12mm glass	Polished Stainless	LLJ-03-PS	•
		Satin Stainless	LLJ-03-SS	•
	Lever Latchset	Polished Stainless	LLG-04-PS	•
	Specify 10mm or 12mm glass thickness	Satin Stainless	LLG-04-SS	•
	Strike Box For Glass Sidelight Specify 10mm or 12mm glass thickness	Polished Stainless	LSG-08-PS	•
		Satin Stainless	LSG-08-SS	•
	Strike Plate For Aluminium or Timber Jambs Specify 10mm or 12mm glass thickness	Polished Stainless	LSJ-09-PS	•
		Satin Stainless	LSJ-09-SS	

GLASS PREPARATION





10/2023 SECTION 3 | COMMERCIAL DOORS, PARTITIONS & PATCH FITTINGS




VIENNA HYDRAULIC HINGES


FH4 VIENNA Hydraulic Hinge Glass to WallNON-HOLD OPENSatin StainlessEH4NHOSSNON-HOLD OPENPolished StainlessEH4NHOPSEH4NHOPSNon-HOLD OPENPolished StainlessEH4NHOPSNon-HOLD OPENPolished StainlessEH4NHOPSNon-HOLD OPENPolished StainlessEH4NHOPSNon-HOLD OPENPolished StainlessEH4NHOPSNon-HOLD OPENPolished StainlessEH4HOPSNon-HOLD OPENPolished StainlessEH4HOPSNon-HOLD OPENPolished StainlessEH4HOPSNon-HOLD OPENPolished StainlessEH4HOPS	•
Fininge opening angle 100 : Self-closing from any angle. Available in non-hold open options. Centre T Style backplate. Polished Stainless EH4NHOPS Max recommended glass weight: 70kg Max recommended door span: 900mm Standard for 12mm glass, can be supplied for 10–15mm on request. HOLD OPEN Satin Stainless EH4HOPS	•
Max recommended glass weight: 70kg Max recommended door span: 900mm Standard for 12mm glass, can be supplied for 10–15mm on request. HOLD OPEN Batin EH4HOPS Folished EH4HOPS	•
supplied for 10–15mm on request. OPEN Polished EH4HOPS	•
Sold AS AT AIX (2X TINges) Stamless	
EH4L VIENNA Hydraulic Hinge Glass to Wall, Offset	•
Wall, Offset OPEN Hinge opening angle 100°. Self-closing from any angle. Available in non-hold open and hold open options. Offset L Polished Stainless EH4NHOLPS	•
Style backplate. Satin Max recommended glass weight: 70kg Stainless Max recommended door span: 900mm HOLD	•
Standard for 12mm glass, can be supplied for 10–15mm on request. *SOLD AS A PAIR (2x Hinges)	•
EH3 VIENNA Hydraulic Satin Hinge Glass to Glass NON-HOLD EH3NHOSS	•
Hinge opening angle 100°. Self-closing from any angle. Available in non-hold open and hold open options. Glass to Cleare Stude.	•
Glass Style. Max recommended glass weight: 70kg Max recommended door span: 900mm Standard for 12mm glass, can be HOLD	•
*SOLD AS A PAIR (2x Hinges) OPEN EH3HOPS	






47 56







Glass-Glass

3

47

56

84

Glass-Wall



180° Glass-Glass



R

DOOR RAILS

DESCRIPTION	INSERT TYPE	GLASS SIZE	FINISH	CODE	PRICE
			ANO	DR10-F12-ANO	
DR10 Bottom Door Rail	Pivoting	10-12mm	Powder Coated	DR10-F12-PC	0
	(to suit)		ANO	DR10-F15-ANO	•
(Non Locking)	Floor Spring	15mm	Powder Coated	DR10-F15-PC	0
Sold by the meter with cover plates and end caps. (min charge = 1mtr)	(Max Floor Spring Capacity 1400mm wide or 300kgs)		ANO	DR10-F19-ANO	•
	wide of SOOKgs)	19mm	Powder Coated	DR10-F19-PC	0
OA Rail length to include 9mm of endcaps (4.5mm each side).			ANO	DR10-P12-ANO	
	Pivoting	10-12mm	Powder Coated	DR10-P12-PC	0
		45	ANO	DR10-P15-ANO	0
	(to suit) Floor Pivot	15mm	Powder Coated	DR10-P15-PC	0
		10	ANO	DR10-P19-ANO	•
		19mm	Powder Coated	DR10-P19-PC	0
	N/A Blank (Sliding/	10, 10,	ANO	DR10-12-ANO	•
		10-12mm	Powder Coated	DR10-12-PC	0
Total door width	Sidlight)	15	ANO	DR10-15-ANO	0
	(NOTE: additional floor guides & roller	15mm	Powder Coated	DR10-15-PC	0
32-38m		19mm -	ANO	DR10-19-ANO	
			Powder Coated	DR10-19-PC	0
	Rail Guide FGR guide for sliding rail		Black Nylon	FGR	•
		10-12mm	ANO	DR20-R12-ANO	•
DR20 Top Door Rail	Pivoting (to suit)	10-12mm	Powder Coated	DR20-R12-PC	0
(Non Locking)	RTS85 Closer	15mm	ANO	DR20-R15-ANO	\bigcirc
Sold by the meter with cover plates	(RTS85 Capacity		Powder Coated	DR20-R15-PC	0
and end caps. (min charge = 1mtr)	1000mm wide Max or 110kgs)		ANO	DR20-R19-ANO	•
OA Rail length to include 9mm of			Powder Coated	DR20-R19-PC	0
endcaps (4.5mm each side).		10-12mm	ANO	DR20-P12-ANO	•
		10 1211111	Powder Coated	DR20-P12-PC	0
	Pivoting (to suit)	15mm	ANO	DR20-P15-ANO	•
	Top Pivot Pin		Powder Coated	DR20-P15-PC	0
		19mm	ANO	DR20-P19-ANO	•
			Powder Coated	DR20-P19-PC	0
	N/A Blank	10-12mm	ANO	DR20-12-ANO	•
	(Sliding/		Powder Coated	DR20-12-PC	0
Total door width	Sidlight) (NOTE:	15mm	ANO	DR20-15-ANO	0
	additional floor guides & roller		Powder Coated	DR20-15-PC	0
32-38mm	attachments available, not included.)	19mm	ANO	DR20-19-ANO	0
	,		Powder Coated	DR20-19-PC	0
	Glass Guide Sliding Door guid frameless glass b	de for	ANO	300967	•



DOOR RAILS

DESCRIPTION	INSERT TYPE	GLASS SIZE	FINISH	CODE	PRICE
			ANO	DR30-F12-ANO	0
DR30 Bottom Door Rail	Pivoting	10-12mm	Powder Coated	DR30-F12-PC	0
	(to suit)		ANO	DR30-F15-ANO	0
(Locking)	Floor Spring	15mm	Powder Coated	DR30-F15-PC	0
Sold by the meter with cover plates and end caps. (min charge = 1mtr)	(Max Floor Spring Capacity 1400mm wide or 300kgs)		ANO	DR30-F19-ANO	
П	wide or 300kgs)	19mm	Powder Coated	DR30-F19-PC	•
OA Rail length to include 9mm of endcaps (4.5mm each side).			ANO	DR30-P12-ANO	•
문제 19 ···································		10-12mm	Powder Coated	DR30-P12-PC	0
	Pivoting	45	ANO	DR30-P15-ANO	•
	(to suit) Floor Pivot	15mm	Powder Coated	DR30-P15-PC	0
			ANO	DR30-P19-ANO	0
		19mm	Powder Coated	DR30-P19-PC	0
		10.10	ANO	DR30-12-ANO	0
	N/A Blank (Sliding/	10-12mm	Powder Coated	DR30-12-PC	0
Total door width	Sidlight)	45	ANO	DR30-15-ANO	•
	(NOTE: additional floor guides & roller	15mm	Powder Coated	DR30-15-PC	0
32-38m	attachments available, not	10	ANO	DR30-19-ANO	
	included.)	19mm -	Powder Coated	DR30-19-PC	0
	Rail Guide FGR guide for sl	iding rail	Black Nylon	FGR	•
		ISIIIII RTS85 Capacity DOOmm wide Max or	ANO	DR40-R12-ANO	
DR40 Top Door Rail	•		Powder Coated	DR40-R12-PC	0
(Locking)	RTS85 Closer		ANO	DR40-R15-ANO	•
Sold by the meter with cover plates	(RTS85 Capacity		Powder Coated	DR40-R15-PC	0
and end caps. (min charge = 1mtr)	1000mm wide Max or 110kgs)		ANO	DR40-R19-ANO	0
OA Rail length to include 9mm of			Powder Coated	DR40-R19-PC	0
endcaps (4.5mm each side).	•	10-12mm	ANO	DR40-P12-ANO	0
	Diveting		Powder Coated	DR40-P12-PC	0
	Pivoting (to suit)	15mm	ANO	DR40-P15-ANO	0
	Top Pivot Pin		Powder Coated	DR40-P15-PC	0
		19mm	ANO	DR40-P19-ANO	0
			Powder Coated	DR40-P19-PC	0
	N/A Blank	10-12mm	ANO	DR40-12-ANO	0
	(Sliding/		Powder Coated	DR40-12-PC	0
Total door width	Sidlight)	15mm	ANO	DR40-15-ANO	0
	(NOTE: additional floor guides & roller		Powder Coated	DR40-15-PC	0
32-38mm	attachments available, not included.)	19mm	ANO	DR40-19-ANO	0
			Powder Coated	DR40-19-PC	0
	Glass Guid Sliding Door guid frameless glass I	de for	ANO	300967	•

NOTE: For Locking Rails specify cylinder Type: DC – Double cylinders, SC - Single Cylinder, CT Cylinder Turn.



GLAZING CHANNEL

PRODUCT	DESCRIPTION	LENGTH	FINISH	CODE	PRICE
		COM4/CS144 Bottom Channel 5mtr Heavy duty one piece architectural		COM4-SA	•
	Commercial channel section, used for interior and exterior applications. Suitable for 15mm to 25mm glass.		Black	СОМ4-ВК	•
	-	Head/Side Channel 5mtr		COM5-SA	•
	တ္ commercial channel section, used for		Black	СОМ5-ВК	•
	00002		Satin Anodised	CS652-SA	•
	Thickness 3mm	5mtr	Black	CS652-BK	•
	Profile: 65x40mm		MILL	CS652-MILL	•
53	CS654 Channel Thickness 3mm		Satin Anodised	CS654-SA	•
8		5mtr	Black	CS654-BK	0
	Profile: 65x65mm		MILL	CS654-MILL	0
43	CS100 Shopfront		Satin Anodised	CS100-SA	•
10 10 10 10 10 10 10 10 10 10 10 10 10 1	Channel Thickness 4mm	5mtr	Black	CS100-BK	0
	Profile:100x55mm		MILL	CS100-MILL	•
	CS105 Shopfront		Satin Anodised	CS105-SA	•
100 100 100	Channel Thickness 4mm	5mtr	Black	CS105-BK	•
	Profile:100x65mm		MILL	CS105-MILL	•



GLAZING CHANNEL

PRODUCT	DESCRIPTION	LENGTH	FINISH	CODE	PRICE
	Heavy duty one piec	COM1/CS134 Bottom Channel 5mtr Heavy duty one piece architectural commercial channel section, used for interior and exterior applications. Suitable for 8, 10, 12 and 15mm glass, can be used with 19mm if wet glazed		COM1-SA	۰
	interior and exterior Suitable for 8, 10, 12			СОМ1-ВК	•
	Head/Side Ch	COM2/CS234 Head/Side Channel 5mtr Heavy duty two-piece architectural		COM2-SA	•
	commercial channel interior and exterior Suitable for 10, 12 ar can be used with 19	applications. nd 15mm glass,	Black	СОМ2-ВК	•
28 3.0 58 3.0 58 3.0 58 3.0 58 58 58 58 58 58 58 58 58 58	CS651 Channel	5mtr	Satin Anodised	CS651-SA	•
	Thickness 3mm Profile: 65x32mm		Black	CS651-BK	0
			MILL	CS651-MILL	•
	CU25/CS25 Channel Thickness 2.5mm		Satin Anodised	CU25-SA	•
		5mtr	MILL	CU25-MILL	0
25mm			Black	CU25-BK	0
2.5/5.0mtr	Profile: 25x20mm		White	CU25-W	0
20mm	_	2.5mtr	Bright Silver	CU25-C	0
			Satin Anodised	CU40-SA	•
	CU40/CS40	Freedo	MILL	CU40-MILL	0
40mm	Channel	5mtr	Black	CU40-BK	0
2.5/5.0mtr	Thickness 2.5mm Profile: 40x20mm		White	CU40-W	0
20mm	_	2.5mtr	Bright Silver	CU40-C	0
45mm	CU45/CS45 C Thickness 2.5mm Profile: 45x20mm	channel	Satin Silver Anodised	CU45-SA	•



10/2023 SECTION 3 COMMERCIAL DOORS, PARTITIONS & PATCH FITTINGS

CHANNEL END CAPS & PARTS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	25.20	Satin Anodised	EC5-SA	•
	25x20mm	Satin Brushed	EC5-SS	•
	40x20mm	Satin Anodised	EC6-SA	\bigcirc
	40x20mm	Satin Brushed	EC6-SS	\bigcirc
	45x20mm	Satin Anodised	EC7-SA	\bigcirc
	45x20mm	Satin Brushed	EC7-SS	\bigcirc
	4Ev22mm	Satin Anodised	EC8-SA	\bigcirc
	45x32mm	Satin Brushed	EC8-SS	\bigcirc
	65x30mm	Satin Anodised	EC9-SA	\bigcirc
		Satin Brushed	EC9-SS	\bigcirc
		Satin Anodised	EC10-SA	\bigcirc
	65x40mm	Satin Brushed	EC10-SS	\bigcirc
	65x55mm	Satin Anodised	EC11-SA	\bigcirc
	000000	Satin Brushed	EC11-SS	\bigcirc
	65x65mm	Satin Anodised	EC12-SA	\bigcirc
		Satin Brushed	EC12-SS	\bigcirc
	100x55mm	Satin Anodised	EC13-SA	\bigcirc
	100x55mm	Satin Brushed	EC13-SS	\bigcirc
	100x65mm	Satin Anodised	EC14-SA	\bigcirc
	iooxooniin	Satin Brushed	EC14-SS	•


PRODUCT	DESCRIPTION	SIZE	CODE	PRICE
	Setting Block Santoprene	15mm x 17mm x 50mm	301044	•
		25mm x 10g Pan Screws Square Drive 304SS	PAN25	•
+	Pan Screws Square Drive	35mm x 10g Pan Screws Square Drive 304SS	PAN55	•
V		50mm x 10g Pan Screws Square Drive 304SS	PAN50	•

PRODUCT	DESCRIPTION	CODE	PRICE	0 0 0
T	10.9 x 4.9mm - Compressed size 4mm (per metre) - Double sided for 12mm Glass with COM1 & 2	301892	•	0 0 0 0 0 0
	11.5 x 4mm - Compressed size 2.5mm (per metre) - Double sided for 15mm Glass with COM1 & 2 - Single sided for 17.5mm Glass with COM1 & 2	302022	•	φ φ φ φ

SETTING BLOCK



STAINLESS FIN BRACKETS




PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
Fin Bracket Set	To support 250mm Fin 250 x 65 x 65 x 6 Specify Glass thickness	Satin Stainless	FB-250	•
Fin Bracket Set	To support 300mm Fin 300 x 65 x 65 x 6 Specify Glass thickness	Satin Stainless	FB-300	•
Special length Fin bracket	65 x 65 x 6 Specify Glass thickness	Satin Stainless	FB-SP	•



10/2023 SECTION 3 COMMERCIAL DOORS, PARTITIONS & PATCH FITTINGS

DOOR SEALS AND COMPONENTS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	Anodised Aluminium Section With polypropylene grey pile. Includes double sided adhesive foam tape. For 12mm thick glass. Length 3000mm	Silver Anodised	DS180-12	•
	Anodised Aluminium Section wWith polypropylene grey pile. Includes double sided adhesive foam tape. For 10mm thick glass. Length 3000mm	Silver Anodised	DS180-10	•
	Clear Polycarbonate Section With black polypropylene pile. For 10mm thick glass. Length 3000mm	Clear Poly	RP103	•
	Clear Polycarbonate Section With polypropylene pile. For 12mm thick glass. Length 3000mm	Clear Poly	RP104	•
	Clear Polycarbonate Section With polypropylene pile. For 15mm thick glass. Length 3000mm	Clear Poly	RP42	•
PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	Sliding Door 90° Seal			




Sliding Door 90° Seal			
Anodised Aluminium Section with polypropylene grey pile. Includes double sided adhesive tape. Seal fitted to back edge of door to create seal back to side panel or wall. Profiles match DS180 seals. When ordering specify dimension 'Y'.	Silver Anodised	DSS90	•
To suit 12mm glass 3000mm length		DSS90-12-Y	•
To suit 10mm glass 3000mm length		DSS90-10-Y	•



DOOR SEALS AND COMPONENTS

PRODUCT

DESCRIPTION



90° Door Seal

This 90° Door Seal provides a seal between Frameless Glass Sliding door panels and sidelights or walls.

Suitable for Manual or Automatic Doors. Slim profile. Will reduce draughts. Will assist with noise reduction. Available for 10mm or 12mm thick glass. Self adhesive. Profile designed to match DS180 edge seal. Available with different woolpile lengths. Supplied in 3000mm lengths.

Silver Anodised Finish with Grey woolpile


PRODUCT	DESCRIPTION	CODE	PRICE
90° Door Seal For 10mm thick glass X = 10mm	Y = 18mm Order	DSS90-10-18	•
	Y = 20mm Order	DSS90-10-20	•
	Y = 23mm Order	DSS90-10-23	•
	Y = 26mm Order	DSS90-10-26	•
	Y = 26mm Order	DSS90-10-26	•
	Y = 28mm Order	DSS90-10-28	•
	Y = 32mm Order	DSS90-10-32	•
90° Door Seal For 12mm thick glass X = 12mm	Y = 18mm Order	DSS90-12-18	•
	Y = 20mm Order	DSS90-12-20	•
	Y = 23mm Order	DSS90-12-23	•
	Y = 26mm Order	DSS90-12-26	•
	Y = 28mm Order	DSS90-12-28	•
	Y = 32mm Order	DSS90-12-32	•

PACKERS AND SETTING BLOCK

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	Silicone Spatula		SP1	۰
	Plastic Packers	Blue	PP1.5	•
	Plastic Packers	Red	PP2	•
	Plastic Packers 3mm	Orange	PP3	•
	Plastic Packers 4mm	Green	PP4	•
	Plastic Packers 5mm	Grey	PP5	•
	Plastic Packers	Black	PP6	•
	Plastic Packers	Brown	PP10	•
	Setting Block Santoprene 15mm x 17mm x 50mm		B12-10	•



TYPICAL DOOR APPLICATION



Fin Requirements

For 10mm glass

As a guide, when the height of the overpanel (A) plus the width of the side panel (B) exceeds a total of 1200mm a support fin is required. A fin is not necessary if either A or B are less than 400mm.

For 12mm glass

As a guide, when the height of the overpanel (A) plus the width of the side panel (B) exceeds a total of 1500mm a support fin is required. A fin is not necessary if either A or B are less than 500mm.

Fins are required to stiffen an assembly from the door action and windloads.

Doors

Maximum recommended sizes

For 10mm glass

Doors with patch fittings	2400h x 1000w
Doors with door rails	2500h x 1100w

For 12mm glass


Doors with patch fittings2700hDoors with door rails2700h


2700h x 1100w 2700h x 1200w


Door Clearances

Recommended clearances are as detailed on drawings.


PATCH FITTING POSITIONS









Looking at outside





Looking at outside







0800 404 043 opushardware.com

